



**MEMO**

1520 E 6<sup>th</sup> Avenue  
PO Box 200901  
Helena MT 59620-0901  
(406) 444-6697 • FAX: (406) 444-3836

**To:** Montana Board of Environmental Review

**CC:** Eric Urban, Water Quality Standards Section Supervisor

**From:** Michael Suplee, Ph.D., and Kyle Flynn, P.H., Environmental Science Specialists, Montana Dept. of Environmental Quality

**Date:** 3/19/2014

**RE:** Benthic algae biomass levels protective of fish and aquatic life in western Montana streams

In Suplee and Watson (2013), an algal biomass value of 125 mg chlorophyll *a*/m<sup>2</sup> is used in western Montana ecoregions to help derive the numeric nutrient criteria for those areas. Excessive bottom-attached algae in streams is a classic symptom of nutrient over-enrichment and controlling such algal growth is one of the objectives of numeric nutrient standards. This memorandum addresses how the 125 mg chlorophyll *a*/m<sup>2</sup> algae biomass value was determined by the Department.

Between 2009 and 2011, the Department carried out a whole-stream nitrogen and phosphorus addition study in a stream in southeastern Montana (Box Elder Creek). The project's objective was to determine what types of impacts to stream beneficial uses occur as a direct result of elevated nutrient concentrations. As documented in Suplee and Sada de Suplee (2011), bottom-attached (benthic) algae grew to much higher levels in the nutrient-dosed reaches than it did in the control reach, reaching a maximum of 127 mg chlorophyll *a*/m<sup>2</sup> of benthic algae<sup>1</sup> in the most highly dosed reach. One of the study's most notable findings was that this high biomass of benthic algae then senesced *en masse* at the end of the growing season, leading to declines in dissolved oxygen (DO) concentration to as low as 1.37 mg/L near the stream bottom. Low DO occurred in what we surmise to be a series of disconnected patches (pools or deposition zones) along the stream bottom; reaches with extremely low DO were found in areas where the stream had slower velocities. It was also documented that the only viable DO sink was the large volume of dead and decaying algae on the stream bottom (confirmed by visual observation and photographs), because water-column BOD<sub>5</sub> samples taken at the time were all less than detection<sup>2</sup>. Thus, elevated nutrient concentrations led to excessive benthic algal growth which, when it senesced and died at the end of the growing season, caused exceedences of the state's dissolved oxygen standards (DEQ, 2012).

<sup>1</sup> This value represents the average for the reach. The reach average was determined from eleven replicate chlorophyll *a* measurements collected systematically at eleven transects spaced along the reach.

<sup>2</sup> Sediment oxygen demand (SOD) was not a significant DO sink in Box Elder Creek as evidenced by the near-saturation levels of water-column DO observed in the control reach throughout the study.

Dissolved oxygen standards are intended to protect fish and associated aquatic life. The finding that unusually high levels of benthic algae can lead to seasonal crashes in DO in wadeable streams is important because it demonstrates a direct link between elevated nutrient concentrations, resultant algae growth, and probable harm to fish and aquatic life that is disconnected in time with the initial nutrient loadings. But because the study was undertaken in southeastern Montana, it was necessary to carry out additional analyses to see if its findings were applicable to western Montana streams, which are generally colder and have steeper gradients.

To explore the effect of water temperature on the DO impacts observed in the eastern Montana study, we developed a modified Streeter-Phelps (1925) analytical model of the Box Elder Creek nutrient dosing reach. The physical basis of the model was then used to evaluate the response of hypothetical streams in western Montana at an elevation of 1,219 m (4,000 ft), with mean daily water temperature of 7 °C (a common temperature in the region), and with varying physical characteristics (gradient and velocities, reflecting different reaeration behavior). Methods, discussion and recommendations are provided below.


## **1.0 Simulation of Nutrient Dosing Study Findings for Cooler Water Temperatures, Higher Dissolved Oxygen Saturation, and Differing Reaeration Rates**

As documented in Suplee and Sada de Suplee (2011), benthic algae senesced *en masse* at the end of the growing season which led to observed DO levels as low as 1.37 mg/L near the stream bottom in the High Dose reach (HD reach) in a depositional area (glide) with steady laminar flow. It was also documented that the only viable DO sink was the large volume of dead and decaying algae on the stream bottom. Thus, senesced algae are a significant and important DO sink when it comes to eutrophication, and we refer to it here as “senesced algae oxygen demand” (SAOD). The terminology has been used to differentiate it from normal sediment oxygen demand (SOD) which is associated with the oxygen consuming properties of organic material in a stream’s bottom sediments.

The questions addressed in this section are:


1. *If the nutrient dosing study had been carried out in an identical western Montana stream but with cooler average temperatures and higher dissolved oxygen saturation, would impacts to Montana’s dissolved oxygen standards still have occurred?*
2. *In the hypothetical stream with cooler water temperatures and higher dissolved oxygen saturation simulated in No. 1 above, what would be the effect of differing reaeration rates on the dissolved oxygen concentrations?*

Continuously monitored data (by YSI 6600 sonde) at the headwaters of the Box Elder High Dose (HD) reach (triangle **A** in **Figure 1-1**, just upstream of the nutrient addition point) showed that DO was very close to saturation entering the HD reach (measured as 8.8 mg DO/L @ 12 cm off the bottom; water temp = 15.3°C; elevation 921 m). By the time water flowed down to the HD reach YSI sonde, DO concentration 12 cm off the bottom had dropped to 1.37 mg/L. The residence time between the two points was about 20 min as identified through velocity measurements. Box Elder Creek is a Rosgen C4 channel (Rosgen, 1996).



**Figure 1-1. Longitudinal diagram of Box Elder Creek high-dose reach.** The upstream YSI sonde (A, on left) was placed just upstream of the point where nutrients were added. There is a span of 110 m between it and the High Dose YSI sonde (B, on right). Two riffles and one pool were found in the reach between the two sondes.

Data indicate that it is unlikely that 1.37 mg DO/L persisted surface to bottom; rather, a vertical gradient in oxygen concentration probably occurred. Such a gradient is typical of steady-state conditions of diffusive mass transfer typified by Fick's first law. Given the mass of decaying algae observed, we inferred that DO was zero mg/L on the bottom of the channel whereas, at the surface, it was still probably at or near saturation (as observed upstream). A simple linear relationship was fit between the three DO-depth points (**Figure 1-2**; representing the linear change in oxygen over depth, i.e.,  $dO_2/dz$ ), and we believe a linear fit is very reasonable. Indeed, if poorly mixed (as typified in diffusion problems) a linear gradient would occur over the water column. In this instance, the linear model most reasonably fits the data.



**Figure 1-2. Estimated surface to bottom DO profile at the HD reach, 12:01 am, 10/6/2010.**

Thus we have some knowledge about the oxygen gradient through the water column as well as the average oxygen concentration at the site in **Figure 1-2** given the previous assumptions. When using the linear assumption, the midpoint between 0 (bottom) and 8.8 (surface) mg DO/L is effectively the mean DO concentration of the site (i.e., 4.4 mg/L). An analytical solution to the Streeter-Phelps model with constant SAOD was then developed. With this new model we could evaluate whether differences in reaeration rates and algae growth rates between eastern and western Montana streams preclude (or do not preclude) the use of an algae level of 125 mg chlorophyll *a*/m<sup>2</sup> to assess aquatic life impacts in western Montana streams. The algae level was slightly lowered, from 127 to 125 mg chlorophyll *a*/m<sup>2</sup>, to provide a threshold that is somewhat more protective; after all, we documented DO impacts at 127. Assuming plug flow (i.e., where advection is dominant) and a channel with uniform slope and cross-sectional area, the 1-D mass balance for DO over a differential element ( $\Delta x$ ) is

$$\Delta V \frac{DO}{dt} = J_{in} A_c - J_{out} A_c \pm \text{reaction}$$

where  $\Delta V$  = volume of element (m<sup>3</sup>),  $A_c$  = channel area (m<sup>2</sup>),  $DO$  = dissolved oxygen concentration (g/m<sup>3</sup>), and  $J_{in}$  and  $J_{out}$  = flux of DO in and out of element due to advection (g/m<sup>2</sup> d). Flux in and out of the element is defined as

$$J_{in} = U(DO)$$

$$J_{out} = U(DO + \frac{dDO}{dx} \Delta x)$$

where  $U$  = channel velocity (m/d) and  $\Delta x$  = incremental distance (m).

By adding first-order reaction rate (i.e., reaeration) and a zero-order term for senesced algae oxygen demand (SAOD [gO<sub>2</sub>/m<sup>2</sup>/d]), the equation looks like

$$\Delta V \frac{DO}{dt} = U(DO) A_c - U(DO + \frac{\partial DO}{\partial x} \Delta x) A_c + k_a (\overline{DO_{sat} - DO}) \Delta V - \frac{SAOD}{H} \Delta V$$

where  $k_a$  = first-order reaeration coefficient (/d),  $\overline{DO_{sat} - DO}$  = the average DO deficit, and  $H$  = channel depth (m).

Collecting terms, dividing by  $\Delta V = A_c \Delta x$ , and taking the limit as  $\Delta x \rightarrow 0$  yields

$$\frac{DO}{dt} = -U \frac{\partial DO}{\partial x} + k_a (\overline{DO_{sat} - DO}) - \frac{SAOD}{H}$$

At this point, it should be noted that the first-order reaeration rate  $k_a$  is actually a function of the liquid mass transfer velocity [ $k_l$ , m/d] divided by  $H$ , which relates atmospheric flux to surface area. Also, because of the high Henry's constant of O<sub>2</sub>, and the fact that oxygen in the atmosphere is constant, exchange is strongly liquid-film controlled. Consequently, DO at saturation ( $DO_{sat}$ ) can be well characterized by altitude and temperature only. Finally, to simplify the differential equation, we reformulate DO concentration as dissolved oxygen deficit  $D = DO_{sat} - DO$  [mg O<sub>2</sub>/L], which switches the

sign of the DO input/output terms. Under steady state conditions the temporal derivative goes away and we are left with

$$0 = -U \frac{dD}{dx} - k_a D + \frac{SAOD}{H}$$

The above differential equation can then be solved by using integrating factors and yields the equation below, where  $D_0$ =the initial DO deficit (mgO<sub>2</sub>/L) and x equals the distance downstream (m) from initial conditions:

$$D = e^{-\frac{k_a}{U}x} \left( D_0 + \frac{SAOD}{Hk_a} \left( e^{\frac{k_a}{U}x} - 1 \right) \right)$$

Finally, substitution of  $k_a$  with the approximation from Owens et al. (1964) makes the equation appropriate for small streams (Covar, 1976) (in metric units, where  $U$  is in m/s):

$$k_a = 5.32 \frac{U^{0.67}}{H^{1.85}}$$


Thus the equation is applicable to small shallow streams where the oxygen generation and consumption processes are primarily reaeration and SAOD. It should be noted that reaeration is temperature adjusted using the Arrhenius equation with a theta ( $\theta$ ) of 1.024 (Chapra, 1997). Also, since we have omitted respiration and photosynthesis from our equation, the results are probably only appropriate for night-time conditions only. Finally, note that algal respiration does consume oxygen in dark reactions through carbon oxidation, but it was not included in the model.

Following model development, we then calibrated the analytical model to data from Box Elder Creek to estimate SAOD expected from an accumulation of dead/decaying algae, which could then be transferred to other streams. In this instance the calibrated SAOD was very high, approximately 92 gO<sub>2</sub>/m<sup>2</sup>/day. Using the Arrhenius equation and a theta ( $\theta$ ) of 1.047 (applicable to BOD decomposition; Chapra, 1997), this zero-order rate equates to 76 gO<sub>2</sub>/m<sup>2</sup>/day at a stream temperature of 7°C. In other words, the biological decomposition rate of the dead algae determined from the Box Elder Creek dosing study has been reduced mathematically to a colder water temperature. We refer to this new, adjusted SAOD as SAOD<sub>COLD</sub>.

**Figure 1-3** below compares the model output for Box Elder Creek vs. the simulated, carbon-copy western Montana stream evaluated through the model. Conditions were kept the same except that the western-Montana simulation was colder (7°C, vs. 15.3°C in Box Elder Cr.) and at a higher elevation (1,219 m vs. 921 m at Box Elder Cr.).<sup>3</sup> In general, we see a longitudinal decline in DO concentration

<sup>3</sup> Velocity in both streams was set at 0.09 m/s, depth at 0.27 m, as measured in Box elder Cr. We also used measured DO (8.8 mg/L) for initial conditions in Box Elder Cr. as observed just upstream of the nutrient-dosed reach (at the sonde shown as A in Figure 1-1); DO at saturation in Box Elder Cr., at 15.3°C and the site elevation, is very close (8.97 mg/L). In the western-MT simulation, DO was set at 10.4 mg/L (saturation at the temp. and elevation given). The  $k_a$  values for Box Elder Creek and its western-MT simulation were 11.1/day and 9.1/day, respectively.

reflective of a waterbody flowing over a very large diffuse SAOD source. The zero-order SAOD used for the western MT stream is  $SAOD_{COLD}$ . The model output presents average water column DO (i.e., the midpoint of the surface-to-bottom DO gradient in **Figure 1-2**) longitudinally, and shows how that average would decline over space due to SAOD. Note that the DO standard is actually exceeded sooner in the western Montana simulation (occurring 75 m downstream as opposed to 100 m in Box Elder Creek). This happens because the western Montana DO standard is set at a higher concentration (8 mg DO/L vs. 5 mg DO/L in much of eastern Montana) because it is intended to protect salmonid fishes.



**Figure 1-3. Model output for two scenarios: (1) Box Elder Creek nutrient dosing study, including YSI sonde data from the HD reach which were used to calibrate the model, and (2) the simulation of an identical stream but at 7°C and at 1,219 m elevation.** Red horizontal lines show the DO standards typical for each region (lower red line for eastern MT, upper red line for western MT).

## 1.1 Simulations Using Different Reaeration Rates

To evaluate the potential effect of the calibrated SAOD presented above, we evaluated a number of stream types commonly encountered in western Montana. The primary difference between the evaluated streams and the Box Elder Creek calibration was the dependence of reaeration rate on channel configuration, and (as before) the effect of colder temperatures and higher altitude on oxygen saturation and biological decomposition rates. Western Montana streams were segregated using the Rosgen stream classification system which integrates factors such as slope, channel width/depth ratio, substrate, etc. Given the dependence of the reaeration coefficient on channel depth and velocity, Manning's equation was used to determine effective velocities for various channel configurations:

$$U = \frac{1}{n} R^{2/3} S^{1/2}$$

where  $U$  = velocity in m/sec,  $R$  = hydraulic radius in m,  $S$  = water surface slope in m/m (Dunne and Leopold, 1978, but in SI units), and  $n$  = Manning's coefficient. Rosgen (1996) provides descriptive statistics for many of his stream types (e.g., C4, F4 channels), and values (e.g., surface water slope, cross-sectional area) representing the central tendency of each group were selected and input into Manning's relationship in order to derive a representative velocity for the stream class group (**Table 1-1**). Roughness coefficients between 0.05 and 0.06 were selected which, from our experience, are reflective of streams during low-flow conditions (recall that the roughness coefficient actually is not independent of flow and depth). Chow (1959) reports variation in Manning's  $n$  with stage and also that weeds (i.e., macrophytes and attached algae) in stream channels induce somewhat higher Manning's  $n$  values. Given that our simulated streams would have fairly thick mats of filamentous algae, slightly higher-than-textbook Manning's  $n$  values are well justified<sup>4</sup>.


**Table 1-1. Stream Channel Characteristics for Different Representative Rosgen Stream Channels Used in the Model.**

Rosgen Stream Type	X-sectional area (m <sup>3</sup> )	Width (m)	Depth (m)	Surface Water Slope (m/m)	Manning's $n$ used	Velocity (m/sec)
<b>B4</b>	1.54	5.77	0.27	0.0200	0.05	1.11
<b>C3</b>	3.09	11.55	0.27	0.0023	0.06	0.32
<b>C4</b>	2.70	10.09	0.27	0.0045	0.06	0.45
<b>C5</b>	2.51	9.39	0.27	0.0005	0.06	0.14
<b>E3</b>	0.88	1.16	0.76	0.0100	0.06	0.80
<b>E4</b>	0.54	0.71	0.76	0.0100	0.06	0.65
<b>E5</b>	0.56	0.73	0.76	0.0010	0.06	0.21
<b>F4</b>	1.95	7.31	0.27	0.0018	0.06	0.28
<b>G4</b>	0.74	2.78	0.27	0.0200	0.06	0.87

The calculated velocities and depths for the stream groups (**Table 1-1**) were used to recalculate the reaeration coefficient in the model and evaluate the effects on longitudinal DO decline. As before, the simulations were run under the assumption that the stream, irrespective of whether it was C4, B4, etc., was at 7°C and at an elevation of 1,219 m. We tested Rosgen B, C, E, F, and G stream types. Following initial testing, it was clear from the B-channel results that the higher gradient A-channels did not need to be evaluated since their gradients/velocities would overcome SAOD. We did not test D channels as Rosgen (1996) provides no descriptive statistics. It was found that C and F channels would be vulnerable to low oxygen problems (i.e., their velocities were insufficient to overcome SAOD<sub>COLD</sub>), the Rosgen C4 channel somewhat less so than C3 or C5. In contrast, A, B, E, and G channels would probably not be impacted by low DO. It is not clear whether D channels would be vulnerable to DO problems or not; some of the lower gradient ones very likely would. **Figure 1-4** below contrasts results from three examples; a hypothetical B4 channel, C3 channel, and F4 channel. As can be seen, high velocities in the B4 channel lead to higher reaeration rates capable of overcoming the SAOD<sub>COLD</sub>; in contrast, the C3 and

<sup>4</sup> Box Elder Creek, which is a Rosgen C4 channel with a D<sub>50</sub> of 45 mm (coarse gravel), required an even higher Manning's  $n$  (0.08) in order to match the Manning's equation result to measured average stream velocity and slopes. Thus, the use of 0.06 in our calculations for Rosgen stream types is quite reasonable.

F4 channel become impacted (relative to their DO standards) in about the same way Box Elder Creek was.



**Figure 1-4. Modeled DO impacts as a function of Rosgen stream class.** Upper Panel. Rosgen B4 channel. Dissolved oxygen would not fall below the 8.0 mg DO/L standard for a long distance and DO impacts are almost certainly negated. Middle Panel. Rosgen C3 channel. Violations of the DO standard occur within 300 m. Lower panel. Rosgen F4 channel. Dissolved oxygen impacts are similar to the C3 channel, but occur in an even shorter distance.



## 1.2 Discussion

Others discuss end-of-growing season senescence of plants and its effect on stream water quality. Jewell (1971) notes in streams in England that “At the end of the growing season, or when the weeds are killed, their decomposition may exert heavy demands on the oxygen resources of a water”. Novotny and Bendoricchio (1989) observe that “oxygen deficiency is highest and most troublesome in streams where shallow productive zones are followed by deeper sections”. The latter statement largely conforms to what we observed, where senesced algae accumulated in the glides and pools of the nutrient-dosed Box Elder Creek reach, and these areas manifested discontinuous areas of low DO longitudinally along the reach.

The reach-average level of benthic algae leading to the DO problem at the Box Elder Creek HD reach ( $127 \text{ mg Chla/m}^2$ ) has been observed in eutrophied streams in western Montana, and quite often *Cladophora* provides a substantial proportion of this biomass (just as was observed in the Box Elder study). Thus, a key biological characteristic of the plains stream we studied, in terms of the biomass and algae type, is quite comparable to western Montana streams. Therefore, we believe it can be reasonably concluded that if the study had been carried out in an identical stream in western Montana, but at  $7^\circ \text{C}$  and with DO at saturation of  $10.4 \text{ mg/L}$ , one would have seen exceedences of the DO standards following a similar pattern.

The SAOD we calculated is far higher than sediment oxygen demand (SOD) reported in the literature (highest SOD located was  $21.4 \text{ g O}_2/\text{m}^2/\text{day}$ ; Ling et al., 2009). But as mentioned at the start, SAOD is not SOD in the normal sense and the rates are not strictly comparable. Novotny and Olem (1994) report that feedlot runoff (a highly organic, putrescible material) can have  $\text{BOD}_5$  of  $1,000\text{--}12,000 \text{ mg/L}$ . If this material were all to settle to the stream bottom in a stream having the same average depth as Box Elder Creek and then exert its DO demand,  $\text{BOD}_5$  values of this magnitude would equate to  $53\text{--}640 \text{ g O}_2/\text{m}^2/\text{day}$  (at  $20^\circ \text{C}$ ). The SAOD we calculated for decomposing benthic algae (equal to  $133 \text{ g O}_2/\text{m}^2/\text{day}$  @  $20^\circ \text{C}$ ) clearly falls to the low side of this range and is, therefore, a reasonable estimate. It should also be noted that the true SAOD may be higher, but much more localized spatially along the reach (i.e., we calibrated it assuming SAOD over the entirety of the reach).

In conclusion, it appears that the Box Elder dosing study, had it been carried out under identical circumstances except for lower water temperature and higher DO saturation, would have led us to similar conclusions about the impacts of senesced algae oxygen demand and associated effects on stream DO dynamics (**Figures 1-2, 1-3**). However, our simulations indicate that the gradients of some western Montana streams are sufficiently high that SAOD can, for all practical purposes, be overcome (**Figure 1-4**, upper panel). Based on our findings, we recommended the following:

1. The  $125 \text{ mg Chla/m}^2$  threshold should apply to all Rosgen C and F channels, as their group characteristics (velocity, depth, etc.) appear to be insufficient to overcome DO impacts from senesced algae oxygen demand;
2. The  $125 \text{ mg Chla/m}^2$  threshold would not apply to Rosgen A, B, E and G channels, as their group characteristics (velocity, depth, etc.) appear to be sufficient to overcome DO impacts from senesced algae oxygen demand; and

3. No recommendation is made for Rosgen D channels at this time. These channels are not so commonly encountered in Montana and cases will need to be evaluated case-by-case.

Note that in streams where the 125 mg Chl $a$ /m<sup>2</sup> threshold does not apply, the recreationally-derived benthic algal threshold (150 mg Chl $a$ /m<sup>2</sup>) does. Because 125 mg Chl $a$ /m<sup>2</sup> links directly to DO impacts, it is associated with the fish and associated aquatic life beneficial use; in contrast, 150 mg Chl $a$ /m<sup>2</sup> applies to the recreation use (per Suplee et al., 2009).

## 2.0 Final Department-recommended Benthic Algae Threshold

A meeting was held between management and technical staff in March 2012 to consider these findings and their implication for making stream assessment decisions. Careful consideration was given to the totality of information provided by the Box Elder nutrient dosing study, the modeling results discussed above, and the benthic algae threshold for protecting the recreation use (150 mg Chl $a$ /m<sup>2</sup>). Our analysis showed that some western Montana streams would be vulnerable to low DO problems if benthic algae reached 127 mg Chl $a$ /m<sup>2</sup>, but other streams would not. There was relatively little difference in magnitude between the level of algae that would prevent impacts to fish and aquatic life (~125 mg Chl $a$ /m<sup>2</sup>) vs. the level which protects recreational (150 mg Chl $a$ /m<sup>2</sup>). Further, monitoring staff who have completed many stream assessments involving benthic algae have indicated that in the vast majority of cases benthic algae levels are either well below or well above the thresholds in question (i.e., borderline cases near the thresholds that would require more detailed analysis and data collection are uncommon). Thus, in order to preclude a complex, two-threshold system requiring Rosgen stream class identification in all cases, the Department instead decided that in western Montana streams a single benthic Chl $a$  threshold of 125 mg Chl $a$ /m<sup>2</sup> (site average) would be used. Values above this threshold are considered impacts to both the aquatic life and the recreational beneficial uses, as documented in Suplee and Sada de Suplee (2011). And as noted at the start of this memorandum, 125 mg Chl $a$ /m<sup>2</sup> has since been used to help derive the proposed base numeric nutrient standards for western Montana ecoregions (Suplee and Watson, 2013; draft Department Circular DEQ-12A).

## 3.0 References

- Biggs, B.J.F., 2000. New Zealand Periphyton Guidelines: Detecting, Monitoring and Managing Enrichment in Streams. Prepared for the New Zealand Ministry of the Environment, Christchurch, 122 p. <http://www.mfe.govt.nz/publications/water/periphyton-guideline-dec2000/index.html>
- Chapra, S.C., 1997. Surface Water Quality Modeling. WCB McGraw-Hill, Boston, Massachusetts, U.S.A.
- Chow, V.T., 1959. Open-Channel Hydraulics, McGraw-Hill Book Co, p. 680.
- Covar, A.P., 1976. Selecting the Proper Reaeration Coefficient for Use in Water Quality Models. Presented at the U.S. EPA Conference on Environmental Simulation and Modeling. April 19-22. Cincinnati, OH.
- DEQ (Montana Department of Environmental Quality), 2012. Circular DEQ-7, Montana Numeric Water Quality Standards, October 2012.
- Dodds, W.K, V.H. Smith, and K. Lohman, 2002. Nitrogen and Phosphorus Relationships to Benthic Algal Biomass in Temperate Streams. Canadian Journal of Fisheries and Aquatic Sciences 59: 865-874.
- Dunne, T., and L.B. Leopold, 1978. Water in Environmental Planning. W.H. Freeman and Company, New York, U.S.A.

- Jewell, W.J., 1971. Aquatic Weed Decay: Dissolved Oxygen Utilization and Nitrogen and Phosphorus Regeneration. *Journal of the Water Pollution Control Federation* 43: 1457-1467.
- Owens, M., Edwards, R., and J. Gibbs, 1964. Some Reaeration Studies in Streams. *Int. J. Air Water Poll.* 8:469-486.
- Ling, T, C. Ng, Lee, N., and D. Buda, 2009. Oxygen Demand of the Sediment from the Semariang Batu River, Malaysia. *World Applied Sciences Journal* 7: 440-447.
- Novotny, V., and G. Bendoricchio, 1989. Linking Nonpoint Pollution and Deterioration. *Water Environment & Technology* 1 (Nov): 400-407.
- Novotny, V., and H. Olem, 1994. *Water Quality: Prevention, Identification, and Management of Diffuse Pollution*. John Wiley and Sons, Inc., New York, U.S.A.
- Rosgen, D., 1996. *Applied River Morphology*. Wildland Hydrology, Pagosa Springs, Colorado, U.S.A.
- Stevenson, R. J., S.T. Rier, C.M. Riseng, and R.E. Schultz, 2006. Comparing Effects of Nutrients on Algal Biomass in Streams in Two Regions with Different Disturbance Regimes and with Applications for Developing Nutrient Criteria. *Hydrobiologia* 561: 149-165.
- Streeter, H.W. and E.B. Phelps, 1925. A Study of Pollution and Natural Purification of the Ohio River, III. Factors Concerning the Phenomena of Oxidation and Reaeration. U.S. Public Health Service. Public Health Bulletin No. 146, February, 1925.
- Suplee, M.W., V. Watson, M. Teply, and H. McKee, 2009. How Green is too Green? Public Opinion of What Constitutes Undesirable Algae Levels in Streams. *Journal of the American Water Resources Association* 45: 123-140.
- Suplee, M.W., and R. Sada de Suplee, 2011. *Assessment Methodology for Determining Wadeable Stream Impairment Due to Excess Nitrogen and Phosphorus Levels*. Helena, MT: Montana Dept. of Environmental Quality.
- Suplee, M.W., and V. Watson, 2013. *Scientific and Technical Basis of the Numeric Nutrient Criteria for Montana's Wadeable Streams and Rivers: Update 1*. Helena, MT: Montana Department of Environmental Quality.